



LOFTOP™ filter cartridges

Eaton's LOFTOP filter cartridges are suitable for a wide range of process application including ultra-pure water, DI and RO water, photo resins, acids, bases, film lacquers, developer, emulsions, magnet dispersions, e-coats and many more.

LOFTOP filter cartridges are made of purity polypropylene fibers. The product includes an integral polypropylene support core.

Features and benefits

- Made of high purity polypropylene fibers (melt-blown)
- No binders or adhesives
- Excellent chemical compatibility
- Available in a variety of end cap/adaptor configurations to fit all industry-standard housings
- Beta rating of 5000, 99.98% efficiency
- Individually sealed in plastic foil
- High dirt-holding capacity
- All materials used meet the FDA requirements according to 21 CFR § 177

Specifications

Filter material
Polypropylene (melt-blown)

Inner core
Polypropylene

End caps
Polypropylene

O-rings
Silicone (standard)
EPDM, FKM, FEP/FKM

Retention ratings
0.50, 1, 3, 5, 10, 20, 50, 90, 120 µm
@ 99.98% efficiency

Technical data

Nominal lengths
10", 20", 30", 40"
(254, 508, 762, 1016 mm)

Outside diameter
2.5" (63 mm)

Inside diameter
1.1" (28 mm)

Max. operating temperature
176 °F (80 °C)

Max. differential pressure
58 psid @ 77 °F (4.0 bar @ 25 °C)


Recommended differential change-out pressure for disposal
35 psid (2.4 bar)



LOFTOP filter cartridges

Flow rate*

(70 °F/21 °C per 10" element for water)



* For liquids other than water, multiply pressure drop by fluid viscosity in centipoise.


Ordering code

Filter type

LT: LOFTOP

Adapter codes

- (): DOE without foamed polyethylene gaskets
- G: DOE with foamed polyethylene gaskets
- 1: SOE 226 O-rings, bayonet/flat
- 2: SOE 222 O-rings, spear
- 3: SOE 226 O-rings, bayonet/spear
- 4: SOE 222 O-rings, flat



Nominal lengths

- 10: 10"
- 20: 20"
- 30: 30"
- 40: 40"

Retention ratings

- 0.5: 0.50 µm
- 1: 1 µm
- 3: 3 µm
- 5: 5 µm
- 10: 10 µm
- 20: 20 µm
- 50: 50 µm
- 90: 90 µm
- 120: 120 µm

Absolute efficiency

(efficiency 99.98%)

O-rings

- (): Silicone
- E: EPDM
- V: FKM
- T: FEP/FKM

North America
44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East
Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altlußheim, Germany
Tel: +49 6205 2094-0
An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

China
No. 3, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Singapore
100G Pasir Panjang Road #07-08
Singapore 118523
Tel: +65 6825-1668

Brazil
Av. Ermanno Marchetti, 1435 -
Água Branca, São Paulo - SP,
05038-001, Brazil
Tel: +55 11 3616-8461

For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration

© 2020 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

EN
EF-LT
06-2020



Powering Business Worldwide

